

Special Series Control Units, Ø22/30mm



BUSB30




BRJ45


Connection, IP65		
Code	Features	Box / Pcs
BUSB	USB Connection, 1,50 Metre	1
BUSB2005	USB Connection, 0,50 Metre	1
BUSB30	Female-Female USB3.0 Connection	10
BRJ45	Female-Female Gold Plated Metal Ethernet Socket	10



SCB22MP1NC1




SCB22MP1RC1




SCB300P6PC1



SCB300P6PCX



SCB30MP7C1



SCB30MP6PSX

Touch Button, IP67						
Code	Body type	Voltage	Type	Connection	Output	
SCB22MP1NC1	Dia 22 mm	10-30 V DC	Momentary	1 Metre Cable	NPN-NO	
SCB22MP1NSX	Dia 22 mm	10-30 V DC	Momentary	M12 Connector	NPN-NO	
SCB22MP1OC1	Dia 22 mm	10-30 V DC	Momentary	1 Metre Cable	NPN-NC	
SCB22MP1OSX	Dia 22 mm	10-30 V DC	Momentary	M12 Connector	NPN-NC	
SCB22MP1PC1	Dia 22 mm	10-30 V DC	Momentary	1 Metre Cable	PNP-NO	
SCB22MP1PSX	Dia 22 mm	10-30 V DC	Momentary	M12 Connector	PNP-NO	
SCB22MP1RC1	Dia 22 mm	10-30 V DC	Momentary	1 Metre Cable	PNP-NC	
SCB22MP1RSX	Dia 22 mm	10-30 V DC	Momentary	M12 Connector	PNP-NC	
SCB22MP5NC1	Dia 22 mm	10-30 V DC	Stay Put	1 Metre Cable	NPN-NO	
SCB22MP5NSX	Dia 22 mm	10-30 V DC	Stay Put	M12 Connector	NPN-NO	
SCB22MP5OC1	Dia 22 mm	10-30 V DC	Stay Put	1 Metre Cable	NPN-NC	
SCB22MP5OSX	Dia 22 mm	10-30 V DC	Stay Put	M12 Connector	NPN-NC	
SCB22MP5PC1	Dia 22 mm	10-30 V DC	Stay Put	1 Metre Cable	PNP-NO	
SCB22MP5PSX	Dia 22 mm	10-30 V DC	Stay Put	M12 Connector	PNP-NO	
SCB22MP5RC1	Dia 22 mm	10-30 V DC	Stay Put	1 Metre Cable	PNP-NC	
SCB22MP5RSX	Dia 22 mm	10-30 V DC	Stay Put	M12 Connector	PNP-NC	
SCB22UP1NC1	Dia 22 mm	10-30 V DC, Optional Lighting Colour, 5 Wired	Momentary	1 Metre Cable	NPN-NO	
SCB22UP1PC1	Dia 22 mm	10-30 V DC, Optional Lighting Colour, 5 Wired	Momentary	1 Metre Cable	PNP-NO	
SCB30MP6NC1	Dia 30 mm	12-30 V DC	Momentary	1 Metre Cable	NPN-NO	
SCB30MP6NSX	Dia 30 mm, Round Shape	12-30 V DC	Momentary	M12 Connector	NPN-NO	
SCB30MP6PC1	Dia 30 mm	12-30 V DC	Momentary	1 Metre Cable	PNP-NO	
SCB30MP6PSX	Dia 30 mm, Round Shape	12-30 V DC	Momentary	M12 Connector	PNP-NO	
SCB30MP7NC1	Dia 30 mm	12-30 V DC	Stay Put	1 Metre Cable	NPN-NO	
SCB30MP7NSX	Dia 30 mm, Round Shape	12-30 V DC	Stay Put	M12 Connector	NPN-NO	
SCB30MP7PC1	Dia 30 mm	12-30 V DC	Stay Put	1 Metre Cable	PNP-NO	
SCB30MP7PSX	Dia 30 mm, Round Shape	12-30 V DC	Stay Put	M12 Connector	PNP-NO	
SCB300P6NC1	Dia 30 mm, Diamond Shape	12-30 V DC	Momentary	1 Metre Cable	NPN-NO	
SCB300P6NSX	Dia 30 mm, Diamond Shape	12-30 V DC	Momentary	M12 Connector	NPN-NO	
SCB300P6PC1	Dia 30 mm, Diamond Shape	12-30 V DC	Momentary	1 Metre Cable	PNP-NO	
SCB300P6PSX	Dia 30 mm, Diamond Shape	12-30 V DC	Momentary	M12 Connector	PNP-NO	
SCB300P7NC1	Dia 30 mm, Diamond Shape	12-30 V DC	Stay Put	1 Metre Cable	NPN-NO	
SCB300P7NSX	Dia 30 mm, Diamond Shape	12-30 V DC	Stay Put	M12 Connector	NPN-NO	
SCB300P7PC1	Dia 30 mm, Diamond Shape	12-30 V DC	Stay Put	1 Metre Cable	PNP-NO	
SCB300P7PSX	Dia 30 mm, Diamond Shape	12-30 V DC	Stay Put	M12 Connector	PNP-NO	
SCB300UP6PC1	Dia 30 mm	12-30 V DC, PLC Control 6 Wired	Momentary	1 Metre Cable	PNP-NO	



HPMR10K2

Potentiometer-Digital Display Ø30 mm (1,5W@70°C IP65)

Code	Range	Number of Turns	Operational Voltage	Output Voltage	Box / Pcs
HPMR01K1	1 kΩ	Multi Turn	24V DC	10 V DC	1
HPMR02K1	2 kΩ	Multi Turn	24V DC	10 V DC	1
HPMR05K1	5 kΩ	Multi Turn	24V DC	10 V DC	1
HPMR10K1	10 kΩ	Multi Turn	24V DC	10 V DC	1
HPMR01K2	1 kΩ	Multi Turn	24V DC	24 V DC	1
HPMR02K2	2 kΩ	Multi Turn	24V DC	24 V DC	1
HPMR05K2	5 kΩ	Multi Turn	24V DC	24 V DC	1
HPMR10K2	10 kΩ	Multi Turn	24V DC	24 V DC	1



BPR01K

Potentiometer Ø22 mm (1,5W@70°C IP65)

Code	Features	Colour	Box / Pcs
BPR01K	1 kΩ (Ceramic, Wired)	●	10
BPR02K	2,2 kΩ (Ceramic, Wired)	●	10
BPR05K	5 kΩ (Ceramic, Wired)	●	10
BPR10K	10 kΩ (Ceramic, Wired)	●	10
BPR100K	100 kΩ (Ceramic, Wired)	●	10
CPPR01K	1 kΩ (Ceramic, Wired) 2,2	●	10
CPPR02K	kΩ (Ceramic, Wired) 5 kΩ	●	10
CPPR05K	(Ceramic, Wired) 10 kΩ	●	10
CPPR10K	(SCeramic, Wired) 100 kΩ	●	10
CPPR100K	(Ceramic, Wired)	●	10



CPPR02K



CPPR05K



RZ3A1A30S2



RZ3A1A60S2

Analogue Time Relays Ø22 mm

Code	Function	Time Range	Operating Voltage	Number of Contacts	Box / Pcs
RZ3A1A30M2	Delay On	0,5-30 min.	10-30V DC	PNP Transistor Output	1
RZ3A1A60M2	Delay On	1-60 min.	10-30V DC	PNP Transistor Output	1
RZ3A1A30S2	Delay On	0,1-30 sec.	10-30V DC	PNP Transistor Output	1
RZ3A1A60S2	Delay On	0,1-60 sec.	10-30V DC	PNP Transistor Output	1



MBZS024S



MBZX220S

Monoblok Buzzer Ø22 mm (LED), 90 db (10 cm Distance) IP50

Code	Features	Nominal Voltage	Box / Pcs
MBZS012S	With LED Illumination	12V AC/DC	10
MBZS024S	With LED Illumination	24V AC/DC	10
MBZS110S	With LED Illumination	110V AC	10
MBZS220S	With LED Illumination	220V AC	10
MBZX012S		12V AC/DC	10
MBZX024S		24V AC/DC	10
MBZX110S		110V AC	10
MBZX220S		220V AC	10

Note: For IP65 preferences, please add "E" letter to end of the code.
In case of IP65 preferences, volume will be decreased 5 db.



S22RGB024PC



S22RGB024PX

RGB LED Ø22 mm IP67

Code	Dia mm	Illumination	Features	Voltage	Colour	Box / Pcs
S22RGB024PC	22	RGB LED	PNP, Cable 1M	RGB LED		1
S22RGB024NC	22	RGB LED	NPN, Cable 1M	RGB LED		1
S22RGB024PX	22	RGB LED	PNP, M12 Connector	RGB LED		1
S22RGB024NX	22	RGB LED	NPN, M12 Connector	RGB LED		1